



2019 HERMISTON RACEWAY
ROAD HOG OFFICIAL RULES

RULES INTERPRETATION:

IF IT DOESN'T SAY YOU CAN, YOU CAN'T

ANY CAR OR EQUIPMENT THAT THE OFFICIALS, BOARD MEMBERS, AND DIRECTORS CONSIDERED EXOTIC OR NOT IN THE BEST INTEREST OF THE TRACK WILL BE CONSIDERED ILLEGAL FOR COMPETITION. IN THE INTEREST OF FAIRNESS, THE RULES MAY BE ADJUSTED TO CREATE A BALANCE OF COMPETITION.

IF NEEDED, FOR COMPETITION PURPOSES THE TRACK CAN MAKE A DECISION TO ADD WEIGHT TO ANY CAR PRIOR TO ENTERING A COMPETITION.

1. This is an open class for 6 and 8 cylinder cars, trucks and wagons.

Years 1960-2010.

No 4th or 5th gen Camaros.

2. 101" minimum wheelbase.

3. Minimum weight 3100 lbs for 8 cylinder ***3000 for 6 cylinder 55% left side weight.

*** this was changed per Greg from 2800 to 3000

4. Ride Heights

A) 6" minimum 9" maximum from bottom of frame rail.

B) OEM lower Spring kits allowed.

C) cutting & heating of Springs ok

D) aftermarket shocks ok

E) no adjustable screw Jack's

5. Seats/Belts

A) race seats required

I) must be mounted to cage, 2 bolt minimum on back of seat, and 4 bolts on bottom of seat with high grade steel bolts no smaller than 1/2" diameter bolt.

II) seat can not be mounted to floor board

B) 5 point harness belts recommended, 4 point ok

I) no more than 5 years old, DO NOT CUT DATE TAGS

II) must be attached to cage

III) no sun damage

IIII) no cracking

IIIII) no rips or tears

6. Window nets required

A) no more than 5 years old, DO NOT CUT DATE TAGS

B) no sun damage

- C) no cracking
- D) no rips or tears

7. Fuel cells recommended, (optional)

- A) if stock tank is behind rear axle, then fuel cell is required.
- B) no aluminum fuel tanks
- C) no plastic tanks
- D) fuel tanks must be properly secured
- E) full metal boat cans ok

8. Tire & wheels

- A) wheels & tires must be stock for the year, make & model of vehicle
- B) snow wheels ok
- C) both left side tires must match size & right side must match size
- D) 60 series minimum & 400 tread wear, no more than 7" tire width of tread.
- E) off set tires & wheels ok IF stock for that year of vehicle
- F) no more than 1" of tire outside of wheel well/fender
- G) drilled brakes ok

9. Body

- A) nerf bars ok, inside of body line (front & rear fender cannot extend beyond either one)
- B) nerf bar must be attached to cage at 2 points
- C) sunroof must be completely covered, with 20 gage steel.
- D) door skinning allowed
- E) inside hood skin removed
- F) must have cotter/hood pins on hood & trunk
- G) if vehicle came with hatch it must remain on vehicle
- H) steel bumpers allowed front & rear

10. Engine compartment

- A) engine/body/frame must be same manufacturer
- B) 500 CFM carburetor max, 2 or 4 barrel (Holly carb ok)
- C) NO antifreeze, wetter water ok
- D) headers allowed maximum of 1 5/8" diameter exit pipe
- E) front hoop drivers choice
- F) cut fender wells ok front & rear
- G) after market distributor ok
- H) intakes must be stock, & NO internal engine building
- I) Fuel injection ok

11. Fire suits & helmets

- A) helmets MUST be SA 2005 or newer
- B) racing approved fore suits, no coveralls. Minimum single layer
- C) boots, tennis shoes or racing shoes ok

12. Ignition

- A) push button recommended, not required
- B) MSD allowed

13. Batteries

- A) secured behind the driver's seat, in a battery box
 - B) kill switch **MUST** be on car, in drivers reach and reach of the safety crew.
- MUST** be labeled ON/OFF in bright color

14. Safety

- A) must have a 2 pound fire extinguisher charged and in drivers reach, but properly secured

15. Transmission

- A) no 6 speed transmissions
- B) automatic transmission with full working torque converter allowed.
- C) drive line must be braced, with safety chain loops or steel loops, and painted white

16. Windshield

- A) stock windshield or Lexan ok, no dirt screen

17. Communication

- A) 2 way communication ok

18. Roll Cages

- A) full cage required **NO** T-bars
- B) if car has nerf bars, required 2 bars on inside above and below nerf bar, 20 gage steel plate attached to outside of cage on drivers side. If no nerf bars require 3 bars on drivers side with 20 gage steel plate attached to the outside of the bars.
- C) passenger side of cage must have 2 horizontal bars or an Xbox
- D) cage must be secured at 4 points, allowed to cut thru floor board to secure to frame if driver

