



2019 HERMISTON RACEWAY STREET STOCK DIVISION RULES

If it doesn't say you can, you can't

Any car or equipment that the officials, board members and directors considered exotic or not in the best interest of the track will be considered illegal for competition. In the interest of fairness, the rules be adjusted to create a balance of competition. If needed, for competition purposes the track can make a decision to add or takeoff weight to any care prior to entering a competition.

Competing Models:

- Any American manufactured V8 passenger car Minimum 101" wheel base.
- NO front wheel drive, NO 4-wheel drive, NO convertibles.
- Front engine cars only. - NO rear or mid-engine cars.
- NO 4th Gen Camaro or firebirds
- 5" ride height minimum (no lower), including side skirts/rocker panels. (measured without driver from the lowest point on the frame. Exhaust and transmission excluded)

Weights:

- Weights are with driver. Can be asked to weigh in at any time.
- 360 cubic inches and less 3100 pounds
- 361 cubic inches and more 3200 pounds (No car will exceed 3400lbs)
- 406 cubic inches is the max allowed.*
- 55% left side max

Cars with aftermarket bodies see provisional section

Roll cage:

- Minimum of 4-point roll cage mandatory and must be fabricated with a minimum of 1 3/4" x .095 round tubing.
- Must have main halo, roof hoop, two a post bars, dash and main hoop spreader bars along with main hoop diagonal bar.
- 4 door bars on left side.
- 10-gauge steel plate must cover all left side door bars and be solidly welded in place.
- Roll cage legs must be attached to frame rails not body.
- Right side door must have at least 2 spreader bars between the A post and the roof hoop and at least one door support to be made of 1 3/4" x .095 round tubing.
- Front and rear hoops are recommended.
- No reinforced bumpers (Front or Rear) . Meaning either stock, OEM or Max 1 3/4 round tubing. -A maximum of two mounts from the frame rails with two side and top supports.

Chassis/ Body:

- Front and rear clips must be stock for make and model.
- Floor pan must be stock or fabricated from minimum 22 gauge and stretch from front to rear firewall. Right side may be cut out for exhaust
- Front firewall maybe removed and replaced but must be in stock location. Right side maybe removed.

- Rear firewall, if not stock may be made of 22-gauge steel
- Roll cage must be securely welded to top rail of frame or on top plate of sub frame.
- Roof height 49" max measured 10" back from windshield
- Rear spoilers 6" by 60" maximum
- Aftermarket front and rear bumpers covers allowed.
- Bodies to be considered stock must have factory steel roof and must have metal rear quarters.

Engines:

- Block must be stock OEM from factory. No aftermarket
- Heads must be stock cast iron straight plug. No angle plug or aluminum. Limit of 2 valves per cylinder. No porting or polishing
- Aluminum intakes ok. No porting or polishing. Single or dual plane.
- Camshaft must be hydraulic or solid flat tappet. No roller cams, No aftermarket shaft rockers. ---No roller lifters.
- Roller rockers allowed
- No fuel injection
- Must use gasoline (race fuel and AVGAS are ok)
- No dry sumps "Single stage pumps ok"
- Flat top pistons only
- Aftermarket rods are allowed
- Engine will be within one inch of center line of crankshaft to center of chassis and number 1 spark plug no farther back than the upper ball joint
- Exhaust manifold or headers allowed. Headers will have 1 3/4" or smaller primary tubes. 3" collector max with dual exhaust system
- NO crossover or 180-degree headers.
- Carb must be 2 barrel or 4412 Holley. Max 1" spacer, 4412 XP carbs not allowed.
- Must have air cleaner
- MSD or equivalent ignition boxes allowed. Aftermarket distributors allowed.
- 602 crates allowed. NO 604.

Transmission/ clutch/ flywheel/rear end:

- No racing transmission. Must be stock OEM manual or automatic.
- Aftermarket shifter and linkage allowed
- Racing clutches allowed
- Light flywheels allowed
- Reverse mounted starter bellhousing allowed
- Aftermarket axles allowed
- No cambered rear ends
- Rear end must be stock OEM or ford 9" (floaters ok, NO quick change)
- Detroit lockers, gold tracks, posi traction allowed
- Drive shaft must be painted white and made of steel. NO aluminum or exotic material

Suspension:

- Non-adjustable tubular upper A arms may be used in place of stock A arms, in stock mounting location
- Lower A arms must be in stock location with stock mounting holes
- No adjustable ball joints
- No rack and pinion unless stock to that year/make/model
- Springs must remain in stock location
- Lowering blocks allowed
- No bump stops
- Steering quickener allowed
- 1-piece sway bar only- must be factory type
- Stock or steel non-adjustable racing struts/shocks only. No externally adjustable. Non-rebuildable. No aluminum
- No coil overs

- No racing spindles. Aftermarket hubs ok
- Steering Centrelink must be stock.
- Swedge tubes/heim ends allowed
- Metric car trailing arms may be moved 3" maximum.
- Pan hard bar- adjustable at frame side only. Must be non-adjustable on rear-end side.
- Shocks must be welded and mounted in stock location
- ***3 link suspensions *** see provisional section
- *** weight jacks *** see provisions section

Brakes:

- Stock OEM brakes with steel calipers only
- No aftermarket.
- Adjustable Proportioning valves ok
- OEM or aftermarket pedals/master cylinders allowed

Wheels and Tires:

- Wheels can be 8" or 10" steel only
- Any new or used 970's or 8" slicks
- 10" takes off with 6/32 tread (take off must be used and not a new scuff. The officials reserve the right to disallow a tire that appear to be new or scuffed only)
- Tires will be checked pre- main event. No pit or adjustments after tech other than air pressure changes in staging area
- No tire softeners
- Must have $\frac{5}{8}$ " wheel studs

Safety:

- Mandatory commercially produced fuel cell (no homemade)
 - Driver's door must be welded/riveted or chained shut
 - No reinforced bumpers (front or rear) meaning either stock oem or max 1 3/4 .095 round tubing. A maximum of two mounts from the frame rails with two side and top supports.
 - Driver's window nets required. (no tears or rips)
 - Must carry a fully charged minimum 2-pound dry chemical or co2 fire extinguisher. Securely mounted within drivers reach (quick release)
 - Side and back glass and body molding must be removed
 - Factory windshield is ok / Lexan recommended
 - Full fire-retardant racing suits required with no tears
 - Racing or Leather nonflammable shoes and gloves required
 - Helmet to be a minimum snell 2005 or SA-2005
 - 4-point racing belts required /5 point recommended up to 5 years old no tears or discoloration
 - Racing seats are required
 - Batteries have to be securely mounted -must have on/off kill switch
- (All safety subject to immediate tech)

Radios / receivers

- Communication is mandatory. MUST have one or the other
- Drivers and spotters must have the capability to hear communications from the track.
- Two-way radios are allowed between driver and spotter (you are responsible for having this prior to event)

****Provisions and additional information: ****

***If car has weight jacks. -Before or during tech they will be marked and tagged with a seal installed by the tech official. Will not be allowed to be adjusted at track after tech. If adjustment is made disqualification will happen. -100lbs added to the cars minimum weight

***Cars with aftermarket bodies -must have a 22-gauge steel plate attached atop entire upper halo plus 50 lbs.

***3 link suspensions- will have maximum left side weight of 54% plus 50 lbs.

***** If there is a car that wants to race at the track and it does not fit these rules, the street stock class and track will vote and agree on provisions needed so that the car may race with the class. ******